



ALIMENTATORE ATX 500W XILENCE PERFORMANCE C XP500R6 PFC ATTI

Description

Output

+3.3V (A): 15

+5V (A): 12

+12V1 (A): 15

-12V (A): 0.3

+5Vsb (A): 3.0

Max. combined power 12V (W): 300

Max. combined power 3.3V + 5V (W): 103

+12V2 (A): 15

Fan / Cooling technology

Bearing technology: Hydro Bearing

Fan size (mm): 120

Protection

OCP (over current protection): –

OVP (over voltage protection): ?

UVP (under voltage protection): ?

SCP (short circuit protection): ?

OTP (over temperature protection): –

OPP (over power protection): ?

Eco / Efficiency

80PLUS certification: –

Efficiency (%) at 230V, 20% load: 85.38

Efficiency (%) at 230V, 50% load: 85.82

Efficiency (%) at 230V, 100% load: 82.67

Environmental directives

ErP: ?

WEEE: ?

RoHS: ?

Cable management / Connectors

Modular cable management: –

Cable length to mainboard (mm): 450

Cable length to first connector (mm): 400

Maximum cable length (mm): 700

Sleeved cables: –

No. of cables: 5

ATX-Motherboard (20+4-pin): 1

P4+4 (CPU): 1

P4 (CPU): –

PCI-E 6-pin (GPU): –
PCI-E 6+2-pin (GPU): 1
PATA 4-pin: 2
SATA 15-pin (HDD, Drives): 4
FDD (Floppy): –
Logistics data, RRP
Range: Performance C
Article number: XN042
EAN code: 4044953500220
Dimensions, package (L x W x H), (mm): 230 x 165 x 100
Gross weight, package (kg): 1.55
Pieces per packaging unit: 10
Dimensions, shipping box (L x W x H), (mm): 18.25
Gross weight, shipping box (kg): 510 x 350 x 250

Meta Fields

SKU : 39.0101

REGULAR PRICE : 36.22