



ALIMENTATORE ATX 650W COOLERMASER MWE GOLD-V2 MPE-6501-AFAA

Description

MODEL
MPE-6501-AFAAG

ATX VERSION
ATX 12V

PFC
Active PFC

INPUT VOLTAGE
90-264V

INPUT CURRENT
8-4A

INPUT FREQUENCY
47-63Hz

DIMENSIONS (L X W X H)
160 x 150 x 86 mm

FAN SIZE
120mm

FAN BEARING
HDB

FAN SPEED
1500 RPM

NOISE LEVEL @ 20%
0 dBA

NOISE LEVEL @ 50%
17.9 dBA

NOISE LEVEL @ 100%
23.4 dBA

EFFICIENCY

90% @ Typical Load

80 PLUS RATING

80 PLUS Gold

ERP 2014 LOT 3

Yes

OPERATING TEMPERATURE

0-50°C

POWER GOOD SIGNAL

100 – 150 ms

HOLD UP TIME

>16ms at 100% Load

MTBF

>100,000 Hours

PROTECTIONS

OVP, OPP, OTP, SCP, OCP, UVP

REGULATORY

TUV, CE, CCC, EAC, RCM, cTUVus, FCC, BSMI

ATX 24-PIN CONNECTORS

1

EPS 4+4 PIN CONNECTORS

1

EPS 8 PIN CONNECTOR

1

SATA CONNECTORS

8

PERIPHERAL 4-PIN CONNECTORS

4

PCI-E 6+2 PIN CONNECTORS

4

SERIES

MWE Gold Series

80 PLUS

Gold

MODULAR

Full Modular

WATTAGE

500 to 750W

Meta Fields

SKU : 39.1952

REGULAR PRICE : 113.18