



ALIMENTATORE ATX 750W COOLERMASER GOLD-V2 80+ MPY-750V-AFBA

Description

MODEL
MPY-750V-AFBAG

ATX VERSION
ATX 12V V2.52

PFC
Active PFC

INPUT VOLTAGE
100-240V

INPUT CURRENT
10-5A

INPUT FREQUENCY
50-60Hz

DIMENSIONS (L X W X H)
160 x 150 x 86 mm

FAN SIZE
135mm

FAN BEARING
FDB

FAN SPEED
1545 RPM

NOISE LEVEL @ 20%
0 dBA

NOISE LEVEL @ 50%
23.6 dBA

NOISE LEVEL @ 100%
32.5 dBA

EFFICIENCY

90% @ Typical Load

80 PLUS RATING

80 PLUS Gold

ERP 2014 LOT 3

Yes

OPERATING TEMPERATURE

0-50°C

POWER GOOD SIGNAL

100 – 500 ms

HOLD UP TIME

17ms

MTBF

>100,000 Hours

PROTECTIONS

OVP, OPP, SCP, OCP, UVP, OTP

REGULATORY

CCC, CE, TUV-RH, RCM, EAC, cTUVus, FCC, BSMI, KC, CB

ATX 24-PIN CONNECTORS

1

EPS 4+4 PIN CONNECTORS

1

EPS 8 PIN CONNECTOR

1

SATA CONNECTORS

12

PERIPHERAL 4-PIN CONNECTORS

4

PCI-E 6+2 PIN CONNECTORS

4

SERIES

V Gold Series

80 PLUS

Gold

MODULAR

Full Modular

WATTAGE

500 to 750W

Meta Fields

SKU : 39.1953

REGULAR PRICE : 147.61