



ALIMENTATORE ATX 750W COOLERMASER MWE750 MPE-7501-ACABW-BEU

Description

MODEL
MPE-7501-ACABW-B

ATX VERSION
ATX 12V V2.52

PFC
Active PFC

INPUT VOLTAGE
200-240Vac

INPUT CURRENT
10-6A

INPUT FREQUENCY
50-60Hz

DIMENSIONS (L X W X H)
140 x 150 x 86 mm

FAN SIZE
120mm

FAN BEARING
HDB

FAN SPEED
2400 RPM

NOISE LEVEL @ 20%
11.12 dBA

NOISE LEVEL @ 50%
20.3 dBA

NOISE LEVEL @ 100%
39.5 dBA

EFFICIENCY

88% Typically

80 PLUS RATING

80 PLUS Bronze EU 230V

ERP 2014 LOT 3

Yes

POWER GOOD SIGNAL

100 – 500 ms

HOLD UP TIME

>18ms at 100% Full [Load@230Vac](#)

MTBF

>100,000 Hours

PROTECTIONS

OVP, OPP, SCP, UVP, OTP

REGULATORY

CCC, CE, TUV-RH, RCM, EAC, cTUVus, FCC, BSMI, KC, CB

ATX 24-PIN CONNECTORS

1

EPS 4+4 PIN CONNECTORS

1

EPS 8 PIN CONNECTOR

1

SATA CONNECTORS

6

PERIPHERAL 4-PIN CONNECTORS

3

PCI-E 6+2 PIN CONNECTORS

4

SERIES

MWE Bronze Series

80 PLUS

Bronze

MODULAR

Non Modular

WATTAGE

500 to 750W

Meta Fields

SKU : 39.5662

REGULAR PRICE : 88.56