



ANTENNA UBIQUITI PBE-5AC-620 POWERBEAM 5GHZ AC 620MM WORLD

Description

Dimensions: 620 x 620 x 386 mm (24.41 x 24.41 x 15.2?)
Weight: 6.4 kg (14.11 lbs)
Power Supply: 24V, 0.5A Gigabit PoE
Max. Power Consumption: 8.5W
Power Method: Passive PoE (Pairs 4, 5+; 7, 8 Return)
Supported Voltage Range: 20-26VDC
Operating Frequency: Worldwide USA: 5150 – 5875 MHz
U-NII-1 USA: 5150 – 5250 MHz
U-NII-2A USA: 5250 – 5350 MHz
U-NII-2C USA: 5470 – 5725 MHz
U-NII-3? 5725 – 5850 MHz
Gain: 29 dBi
Networking Interface: (1) 10/100/1000 Ethernet Port
Processor Specs: Atheros MIPS 74Kc, 720 MHz
Memory: 128 MB DDR2, 16 MB Flash
LEDs: (1) Power, (1) LAN, (4) WLAN
Signal Strength LEDs: Software-Adjustable to Correspond to Custom RSSI Levels
Max. VSWR: 1.6:1
Channel Sizes: PtP Mode: 10/20/30/40/50/60/80 MHz
PtMP Mode: 10/20/30/40 MHz
Polarization: Dual Linear
Enclosure: Outdoor UV Stabilized Plastic
Mounting: Pole-Mount (Kit Included)
Wind Loading: Radome Excluded: 1510 N @ 200 km/h (340 lbf @ 125 mph)
Radome Included: 1830 N @ 200 km/h (411 lbf @ 125 mph)
Wind Survivability: 200 km/h (125 mph)
ESD/EMP Protection: Air: ± 24 kV, Contact: ± 24 kV
Operating Temperature: -40 to 70° C (-40 to 158° F)
Operating Humidity: 5 to 95% Noncondensing
Wireless Approvals: FCC, IC, CE
RoHS Compliance: Yes
Salt Fog Test: IEC 68-2-11 (ASTM B117), Equivalent: MIL-STD-810 G Method 509.5
Vibration Test: IEC 68-2-6
Temperature Shock Test: IEC 68-2-14
UV Test: IEC 68-2-5 at 40° C (104° F), Equivalent: ETS 300 019-1-4
Wind-Driven Rain Test: ETS 300 019-1-4, Equivalent: MIL-STD-810 G Method 506.5

Meta Fields

SKU : 52.598

REGULAR PRICE : 261.36