



BAREBONE SERVER ASUS 4U TS100-E10-PI4 1XLGA1151 4XDDR4 ECC M

Description

***** Attenzione: trattasi di barebone, non contiene CPU/RAM/Storage/OS *****

Specifiche

Processore / Bus di Sistema

- 1 x Socket LGA1151
- Intel® Xeon® processor E-2100 family(95W)
- Intel® Core™ i3 processors
- Intel® Pentium™ processors
- Intel® Celeron™ processors
- Intel® Xeon® E Processors
- *Refer to support page for more information

Generation

E10

Core Logic

Intel® C242 Chipset

Memoria

Total Slots : 4 (2-channel)

Capacity : Maximum up to 64GB UDIMM

Memory Type : 2666/2400 UDIMM non ECC and with ECC

Memory Size : 16GB, 8GB, 4GB

* Refer to support page for more information

Slot di Espansione

- 1 x PCI-E x16 (Gen3 x16 Link)
- 1 x PCI-E x8 (Gen3 x4 Link)
- 2 x PCI

Storage

SATA Controller :

Intel® C242 Chipset

6 x SATA3 6Gb/s ports + 2 x M.2 connector *1

Intel® Rapid Storage Technology Enterprise(RSTe) (For Linux/Windows)
(Support Software RAID 0, 1, 5, 10)

SAS Controller :

ASUS PIKE II 3008 8-port SAS HBA card

Drive Bays

3 x Internal 3.5" (or 2 x 2.5" optional cage) drive bays*
1 x Internal 2.5" drive bay
1 x Optional internal 5.25" to 3.5"/2.5" drive cage

* Support only 1 drive when add-on card over 9.5" installed on x16 link slot

2 x M.2 (NGFF 22110/2280/2260/2242. One supports both SATA 6Gb/s & PCI-E Gen3 x2 link, the other is SATA 6Gb/s only.)

Storage aggiuntivo FDD/CD/DVD

2 x 5.25" media bays

Options: No Device / DVD-RW / DVD ROM

Networking

1 x Intel® I210AT
1 x i219-LM

Grafica

Aspeed AST2510 with 64MB VRAM

Porte I/O Pannello Frontale

2 x USB 3.0 ports
2 x USB 2.0 ports
1 x Headphone port
1 x Microphone port

Rear I/O Ports

2 x USB 3.1 ports
2 x USB 3.0 ports
2 x USB 2.0 ports
1 x VGA Port (onboard Aspeed AST2510)
2 x LAN Ports
3 x Audio Jacks (onboard Realtek® ALC887-VD2 8-Channel High Definition Audio CODEC)
1 x PS/2 Keyboard/ Mouse Port

Switch/LED

Front Switch/LED:

1 x Power switch
1 x Power LED
1 x Reset switch
1 x HDD Access LED

Soluzione di Gestione

ASUS Control Center

Dimensioni

423mm x 190mm x 435mm

Formato

Tower

Alimentatore

500W 80PLUS Single Power Supply, Gold
Rating: 100-240Vac, 7-3.5A, 50/60Hz, Class I

Note

*1
Intel® C242:
6 x SATA 6Gb/s ports with 2 x M.2 (NGFF 22110/2280/2260/2242, gray SATA port will disable when M.2 is SATA signal)*
Intel® RSTe (Windows & Linux)
(Support software RAID 0, 1, 10 & 5)

* One supports both SATA 6Gb/s & PCI-E Gen3 x2 link, the other is SATA 6Gb/s only.

ATTENZIONE

Le caratteristiche tecniche descritte in questa pagina sono relative alle Serie dei prodotti commercializzati da ASUS a livello internazionale e non necessariamente corrispondono a quelle presenti sui Singoli Modelli commercializzati in Italia. Le caratteristiche tecniche riportate sono quindi da ritenersi indicative e soggette a cambiamento senza preavviso. Per ottenere informazioni su prezzi e configurazioni relative ai modelli commercializzati sul territorio nazionale, suggeriamo di consultare il listino prezzi al seguente indirizzo <http://www.asusworld.it/macrocategory.asp?asusit=1>.

Meta Fields

SKU : 01.653

REGULAR PRICE : 481.78