



BAREBONE SERVER ASUS 5U TS300-E10-PS4 1XLGA1151 4XDDR4 ECC M

Description

***** Trattasi di Barebone: non sono presenti: CPU/Ram/Storage/OS *****

Specifications

Processor / System Bus

1 x Socket LGA1151

Intel® Xeon® E Processors

*Refer to support page for more information

Generation

E10

Core Logic

Intel® C246 Chipset

Memory

Total Slots : 4 (2-channel)

Capacity : Maximum up to 64GB UDIMM

Memory Type : DDR4 2666/2400

Memory Size : 16GB, 8GB, 4GB

* Refer to support page for more information

Expansion Slots

Total PCI/PCI-X/PCI-E/PIKE Slots: 4+1

1 x PCIe 3.0 x16 slots (@x16/8 link)

1 x PCIe 3.0 x8 slots (@ x8 link)

1 x PCIe 3.0 x8 slot (@x4 link)

1 x PCI slot

1 x MIO slot for Audio Card

Storage

SATA Controller :

Intel® C246 Chipset

8 x SATA3 6Gb/s ports

Intel® Rapid Storage Technology Enterprise(RSTe) (For Linux/Windows)

(Support Software RAID 0, 1, 5, 10)

SAS Controller :

- ASUS PIKE II 3008-8i 8-port SAS 12G RAID card
- ASUS PIKE II 3108-8i 8-port SAS 12G HW RAID card

HDD Bays

- 4 x Hot-swap 3.5/2.5" HDD Bays
- Optional(additional 4 x HDD bays)

Auxiliary Storage FDD/CD/DVD

- 4 x 5.25" media bays
- (Options: No ODD/DVD-RW)
- (DVD-RW default for North America)

Networking

- 4 x Intel® I210AT + 1 x Mgmt LAN

Graphic

- Aspeed AST2500 with 64MB VRAM

Front I/O Ports

- 2 x USB 3.1 Gen1 ports
- 2 x USB 2.0 ports
- 1 x Audio out port (with optional MIO card)
- 1 x MIC in port (with optional MIO card)
- 1 x Power Button
- 1 x Reset Button

Rear I/O Ports

- 5 x RJ-45 ports (One for ASMB9-iKVM)
- 2 x USB 3.1 Gen2 ports
- 2 x USB 3.1 Gen1 ports
- 1 x Internal A Type USB Port
- 1 x VGA port
- 1 x COM port

Switch/LED

- Front LED:
 - 1 x Power LED
 - 1 x Location LED
 - 1 x HDD Access LED
 - 1 x Message LED
- LAN 1-4 LED

OS Support

- Please find the latest OS support from https://www.asus.com/event/Server/OS_support_list/OS.html

Management Solution

- ASUS Control Center
- Optional ASMB9-iKVM for KVM-over-IP

Regulatory Compliance

- BSMI, CE

Dimensions

- 445mm * 217.5mm * 545mm

Form Factor
5U/Tower

Weight
Net Weight: 15.0 Kg
Gross Weight: 18.9 Kg

Power Supply
500W 80PLUS Single Power Supply, Gold
Rating: 100-240Vac, 7-3.5A, 50/60Hz, Class I

Environment
Operation temperature: 10° ~ 35°
Non operation temperature: -40° ~ 70°
Non operation humidity: 20% ~ 90% (Non condensing)

Meta Fields
SKU : 01.652
REGULAR PRICE : 803.86