



CONTROLLER RAID ASUS PIKE II 3108-8i/240PD SATA/SAS 12GB/S –

Description

ASUS PIKE II 3108-8i/240PD/2G (Max. Physical Disk Qty for RAID: 240) is the latest 12Gb/s SAS and PCI-E 3.0 high reliability enterprise storage solution. It meets user needs with support for 6Gb/s SATA and 12Gb/s SAS storage and integrated RAID 0, RAID 1, RAID 10, RAID 5, RAID 50, RAID 6 and RAID 60 data protection. Just placing the PIKE card can immediately enlarge the capacity and improve the performance, making it the great upgrade option.

Controller

Broadcom (LSI) SAS3108

Host Interface

PCIe 3.0 x8

Ports

8 internal ports by 2 Mini-SAS HD connectors

RAID Level Supported

0, 1, 10, 5, 6, 50, 60

Devices Supported

SATA Devices

SAS Devices

Data Transfer Rate

Max. SAS 12Gb/s

Max. SATA 6Gb/s

Embedded Memory

2GB DDR3

JBOD Mode

Yes/

Cache Protection

Optional LSI CacheVault 2G

ASUS Ordering Part Number: 90SKC000-M13AN0

Form Factor

Low-profile Card

Dimensions

6.6 x 2.71 Inch

Package Content

1 x Full-height Bracket (Default)
1 x Low-profile Bracket
1 x Driver Disc

Note

* Max. physical Disk qty for RAID: 240

* The card only works with ASUS Server/Workstation motherboards and systems.

* Support Physical Key for MegaRAID CacheCade Pro 2.0 Software

Avago Physical Key Ordering Part Number: LSI00290

<http://www.avagotech.com/products/server-storage/raid-controllers/megaraid-cachecade-pro-software#overview>

Meta Fields

SKU : 38.461

REGULAR PRICE : 492.45