



EXTENDER 10/100MBPS POE ATLANTIS A02-POE-EXT – GARANZIA 2 AN

Description

Product Name
NetPower EXT1

Code
A02-PoE-Ext

Standard
IEEE 802.3 10BASE-T Ethernet
IEEE 802.3u 100BASE-TX Fast Ethernet
IEEE 802.3af (Mode A) [PoE: pin 3,6 for power- and pin 1,2 for power+] Power OUT
IEEE 802.3af (Mode A) [PoE: pin 3,6 for power- and pin 1,2 for power+] Power IN
IEEE 802.3af (Mode B) [PoE: pin 7,8 for power- and pin 4,5 for power+] Power IN
IEEE 802.3at (Mode A/B) Power IN
IEEE 802.3x Flow Control

Network Media
• 10Base-T: UTP category 3, 4, 5 cable Unshielded Twisted Pair (UTP) Cable
• 100Base-TX: UTP category 5, 5e cable Unshielded Twisted Pair (UTP) Cable
• PoE port: UTP category 5 Unshielded Twisted Pair (UTP) Cable

Protocol
CSMA/CD

Ports
• 1 x 10/100 Mbps Auto-Negotiation, Auto-MDIX PoE Port IN (802.3at A/B and 802.3af A/B)
• 1 x 10/100 Mbps Auto-Negotiation, Auto-MDIX PoE Port OUT (802.3af A)

Network Data Transfer Rate
Ethernet: 10Mbps (half duplex), 20Mbps (full duplex)
Fast Ethernet: 100Mbps (half duplex), 200Mbps (full- duplex)

Diagnostic LEDs
Power, Link/ACT, PoE

PoE (OUT)
• Up to 15,4W per port (Mode A)
• PD classification identify
• PoE Over Current Protection

- PoE Circuit Sorting Protection

PoE (IN)

- Up to 30W per port (Mode A/B)

Internal Power Adapter

- 100-240 V AC/50-60Hz

Power Consumption

- 2.6 Watt (Maximum without PD device connected)
- 18 Watt (Maximum with 15,4W PoE device connected)

Noise level

Less 40 dB

Dimensions (WxHxD)

95mm × 70mm × 25mm

Weight

185 g

Temperature Range

- Operation: 0°C ~ 32°C
- Storage: -10°C ~ 60°C

Humidity

- Operation: 10% ~ 90% non-condensing
- Storage: 5% ~ 95% non-condensing

Meta Fields

SKU : 43.1174

REGULAR PRICE : 64.42

SALE PRICE : 51.53