



LETTORE BARCODE DA TAVOLO ATLANTIS A08-OLD68-2D USB-TEC.OTTI

Description

Optical

Optical sensor: Optical Sensor 752(H) x 480(V) Wide VGA

Light source + Illumination: 625 nm Aiming LED + illumination 630nm LED

Resolution: 4 mil (code39), 7,5 mil (Datamatrix), 5 mil (PDF 417)

Depth of Field: up to 267mm

Field of view: 46.1° Horiz – 30,4° Vertical

Electrical

Voltage: +5V±5%

Scanning currents: Standby currents: Power Consumption: 1,4 wats

Environment

Operating temperature: 0°C to 40°C / 32°F to 104°F

Storage temperature: -40°C to 70°C / -40°F to 140°F

Light level: Maximum 86,100 Lux. (direct sunlight)

Operating humidity: 95% RH, non-condensing at 122° F/50° C

Storage humidity: 85% RH, non-condensing at 158° F/70° C

Shock resistance: 1.5m drops

Physical

Weight: 300g(w/cable)

Dimensions: 140mm(L)x73mm(W)x70mm(H)

Housing Material: ABS plastic

Cable Lenght: ~ 150 cm

Codici a barre supportati

(1D)

UPC/EAN/(UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN-13 plus supplemental

ISBN

ISSN

Coupon Code)

Code 39

Code 39 Full ASCII

Trioptic

Code 32 (Italian Pharmacode)

Code 128

(Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated)

Code 93

Codeabar/NW7

Interleaved 2 of 5

Descrete 2 of 5

IATA Chinese 2 of 5

Matrix 2 of 5

Code 11

MSI Plessey

GS1Databar

(Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)

(PDF417 var) PDF417 (Standard, Macro)

MicroPDF417 (Standard, Marco)

Composite Code (CC-A, CC-B, CC-C)

(2D)

MaxiCode

Data Matrix

Data Matrix inverse

QR Code

QR Inverse

Micro QR Code

Aztec Code

Aztec Inverse

Postal Code

(Postal) U.S. Posnet and Planet

U.K. Post

Japan Post

Australian Post

Netherlands KIX Code

Royal Mail 4 State Customer

UPU FICS 4 State Postal

USPS 4CB

Meta Fields

SKU : 87.355

REGULAR PRICE : 288.41

SALE PRICE : 245.15