



LETTORE BARCODE OMNIDIR. ATLANTIS A08-OLS15 TECNOL.LASER –

Description

Optical

Optical sensor: Omnidirectional Laser

Light source: Laser diode(650nm)

Resolution: 4 mil (code39), 7,5 mil (Datamatrix), 5 mil (PDF 417)

Depth of Field: up to 216mm (EAN) @ 13mil, 90% PCS

Scan Rate: 200 scans/sec – 20lines pattern

Electrical

Voltage: +5V

Scanning currents:0.32A

Standby currents: 0.23A

Power Consumption: 1,6 wats

Environment

Operating temperature: 0°C to 40°C / 32°F to 104°F

Storage temperature: -20°C to 60°C / -4°F to 140°F

Light level: Max 5.000 LUX

Operating humidity: 95% RH, non-condensing

Storage humidity: 85% RH, non-condensing at 158° F/70° C

Shock resistance: No

Physical

Weight: 380g

Dimensions: 107mm(D)x95mm(W)x145mm(H)

Housing Material: ABS

Cable Lenght: 1.8 m

Codici a barre supportati

(1D)

UPC/EAN/(UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN-13 plus supplemental

ISBN

ISSN

Coupon Code)

Code 39

Code 39 Full ASCII

Trioptic

Code 32 (Italian Pharmacode)

Code 128

(Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated)

Code 93

Codeabar/NW7

Interleaved 2 of 5

Discrete 2 of 5

IATA Chinese 2 of 5

Matrix 2 of 5

Code 11

MSI Plessey

GS1 Databar

(Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)

(PDF417 var) PDF417 (Standard, Macro)

MicroPDF417 (Standard, Macro)

Composite Code (CC-A, CC-B, CC-C)

(2D)

Optical

Optical sensor: Optical Sensor 752(H) x 480(V) Wide VGA

Light source + Illumination: 625 nm Aiming LED + illumination 630nm LED

Resolution: 4 mil (code39), 7,5 mil (Datamatrix), 5 mil (PDF 417)

Depth of Field: up to 267mm

Field of view: 46.1° Horiz – 30,4° Vertical

Electrical

Voltage: +5V±5%

Scanning currents: Standby currents: Power Consumption: 1,4 wats

Environment

Operating temperature: 0°C to 40°C / 32°F to 104°F

Storage temperature: -40°C to 70°C / -40°F to 140°F

Light level: Maximum 86,100 Lux. (direct sunlight)

Operating humidity: 95% RH, non-condensing at 122° F/50° C

Storage humidity: 85% RH, non-condensing at 158° F/70° C

Shock resistance: 1.5m drops

Physical

Weight: 300g(w/cable)

Dimensions: 140mm(L)x73mm(W)x70mm(H)

Housing Material: ABS plastic

Cable Length: ~ 150 cm

Codici a barre supportati

All UPC/EAN/JAN

EAN128 Code

Code 39

Code 39 Full ASCII

Code32 / Italian Pharmacy

Code 128

CODABAR/NW7

Interleave 25

Industrial 25

Matrix 25

MSI/PLESSEY

Telepen

Code 93

Code 11

China Postage

GS1 DataBar

Meta Fields

SKU : 87.356

REGULAR PRICE : 218.14

SALE PRICE : 207.23