



MODEM 56K USB ESTERNO V90/92 CONEXANT ATLANTIS A01-PU3 -GARA

Description

Modem Features

USB Interface 1.1

ITU-T V.92* Data/Fax modem

CDC-compliant and supported by Microsoft CDC modem drivers

Supports data/fax/TAM operation with hardware-based modem controller, digital signal processing, and DAA/telephone line interface functions

Quick Connect, Modem-on-Hold ** and 48Kbps PCM upstream supported for ITU-T V.92

Automatic detection between data/fax calls

Line quality monitoring and re-train

Enhanced ADPCM/PCM voice operation with concurrent DTMF detection

Chipset Solution

Based on Conexant 4th Generation Smart DAA chipset configuration

Data mode Features

56Kbps Internet connectivity via ITU/TIA V.92 standard

DTE rate of up to 460,800 bps (via Virtual UART)

Data Modem Standard

V.90/V.92 : 56Kbps

V.34bis: 33.6Kbps

V.34: 28.8Kbps

V.32bis : 14.4Kbps

V.32, V.23, V.22bis, V.22, V.21

Bell 103 and Bell 212A

Data Compression

V.44

V.42bis, MNP 5

Error Correction

V.42, LAPM, MNP 2-4

FAX Modulations

V.17: 14.4Kbps

V.29: 9,600 bps

V.27ter :4,800 bps

FAX Control / Protocol
Class 1, V.21 Channel 2
Group 3 fax mode

USB Features
Compatible with both USB 1.1 and USB 2.0 host controllers and hubs
Supports Suspend/Resume
Bus Powered, does not require external power supply

Drivers Support
Windows® 98SE, Windows® 2000, Windows® Millennium, Windows® XP
Windows Vista 32TM

NETWAITING™
Accept call and put modem on hold, or reject call and continue Internet session (V.92 only).
Allow the user to place outgoing calls by putting the modem on hold if an Internet connection is engaged (V.92 only).

Physical and Environmental
Storage Temperature: -10~50°C
Operating Temperature: 5~40°C
Humidity: 20% – 85% RH, no condensation
Dimensions: 74 mm x 18 mm x 26 mm (without USB Cable)
Weight: 35 g

System Requirements
Pentium® MMX 233MHz with 128MB RAM for Windows® 2000 / Windows® XP
Available USB Port
CDRom Drive
10MB available hard disk space (system files and modem drivers only)

Package Contents
WebRunner USB V.90/V.92 56K Modem
Installation CD with Driver, Manuals and NetWaiting
Telephone Extension Cable RJ-11
Quick Start Manual

* V.92 feature is subjected to ISP support
** requires software application support

Meta Fields

SKU : 44.112

REGULAR PRICE : 9.96

SALE PRICE : 6.97