



MODEM ADSL2+ ROUTER ICHONA ART21GSU 1P ETHERNET RJ45 + 1P U

Description

ADSL

- ANSI T1.413 issue 2
- ITU-T G.992.1 (G.dmt)
- ITU-T G.992.2 (G.lite)
- G.994.1 (G.hs, Multimode)
- ITU-T G.992.3 (ADSL2 G.dmt.bis)
- ITU-T G.992.4 (ADSL2 G.lite.bis)
- ITU-T G.992.5 (ADSL2+)
- Reach Extended ADSL (RE ADSL)

Protocolli ATM e PPP

- ATM Forum UNI 3.1/4.0 PVC
- Support up to 8 PVCs
- Traffic Shaping UBR, CBR, VBR-nrt
- Multi Protocol over AAL5 (RFC1483 / 2684)
- Classical IP over ATM (RFC 1577)
- RFC2516 (PPP over Ethernet)
- RFC2364 (PPP over ATM)
- VC and LLC Multiplexing
- OAM F4 and F5 segment end-to-end loopback
- VPI is 0-255 and VCI is 1-65535

Bridging / Routing

- Ethernet to ADSL self-learning Transparent Bridging (IEEE802.1D)
- Support up to 128 MAC learning addresses
- IP routing-RIPv2 (backward compatible with RIPv1)
- Static IP routing

- Routing:IP/UDP/TCP/ARP/RARP)
- ICMP (Internet Control Message Protocol)
- IGMP (Internet Group Management Protocol)
- PAT (Port Address Translation)

IP Management

- NAT (Network Address Translation): up to 1024 NAT translation session
- NAPT (Network Address and Port Translation)
- DHCP Server/Relay/Client
- DNS Proxy
- Dynamic DNS
- UPnP support

Sicurezza

- PPP over PAP (Password Authentication Protocol: RFC1334)
- PPP over CHAP (Challenge Authentication Protocol: RFC1994)
- Packet Filtering / Bridge Filter
- Password Protected System Management
- Firewall

Gestione HTTP Web-based

- Web-based GUI Configuration / Management
- Command-line Interpreter (CLI)
- Telnet Remote Management
- Firmware upgrade via FTP / TFTP
- SNMP Support
- Built-in Diagnostic tool

Dimensioni e Peso

- 125mm(length) x 88mm (width) x 27mm (height)
- circa 140g

Interfacce

- One USB port compliant with USB v1.1, full speed (12Mbps)
- One RJ45 ports compatible with IEEE 802.3/802.3u
- 10/100Mbps auto selection
- One RJ11 port for ADSL connection
- One reset button for restoration of factory default setting

Sistemi Operativi Supportati

- Windows 98,98SE, ME, 2000, XP, MAC, Linux

Requisiti di alimentazione

- Power Adapter: Input 110 $\pm$ 10 or 230 $\pm$ 10 VAC, Output 9VAC 1000mA

Specifiche Ambientali

- Operating temperature: 0°C ~ 70°C ambient
- Humidity: 5 % ~ 95 % (non-condensing)
- Storage temperature:-40°C ~ 70°C

Certificazioni

- FCC part 15, CE, LVD

Meta Fields

SKU : 43.467

REGULAR PRICE : 8.76

SALE PRICE : 8.58