



POE INJECTOR GBPS UBIQUITI U-POE-AF 802.3AF

Description

Dimensions: 86 x 46 x 33 mm (3.39 x 1.81 x 1.30")

Weight: 100 g (3.53 oz)

Output Voltage: 48VDC @ 0.32A

LAN Activity Indicator: No

Gigabit LAN Port: Yes

Remote Reset Capability: Yes

Reset Button: No

Rated Voltage: 100-240VAC @ 50/60Hz

Input Current: 500mA @ 90VAC

Inrush Current: Efficiency: 84.25+%

Output Ripple: 200mV p-p

Switching Frequency: 65 kHz

Line Regulation: ? 3%

Load Regulation: ? 5%

2-Pair Powering: Pins 4, 5 (+) and Pins 7, 8 (-)

Operating Temperature: 0 to 40° C (32 to 104° F)

Storage Temperature: -30 to 70°C (-22 to 158° F)

Operating Humidity: 5 to 90% Noncondensing

AC Connector: IEC-320 C6

Data IN / POE: RJ45 Shielded Socket

Surge Protection: Difference and Common Mode

Clamping Protection: 11V Data, 60V Power

Max. Surge Discharge: 1500A (8/20 μs) Power

Peak Pulse Current: 36A (10/1000 μs) Data

Shunt Capacitance: Response Time: Certifications: CE, FCC, IC, UL

Meta Fields

SKU : 52.589

REGULAR PRICE : 8.98