



SWITCH 16P LAN GIGABIT TP-LINK TL-SG1016DE EASY SMART-MTU/PO

Description

Standards e protocolli: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p

Interfaccia: 16 10/100/1000Mbps RJ45 Ports

AUTO Negotiation/AUTO MDI/MDIX

Cablaggio: 1

- 0BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100O STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100O STP (maximum 100m)
- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)
- EIA/TIA-568 100O STP (maximum 100m)

Dimensioni (LxPxA): 11.6*7.1*1.7 in. (294*180*44 mm)

Ventilazione: Fanless

Alimentatore: 100-240VAC, 50/60Hz

PRESTAZIONI

Switching Capacity: 32Gbps

Tavola indirizzi MAC: 8K

Packet Buffer Memory: 512KB

Packet Forwarding Rate: 23.8Mpps

Jumbo Frame: 10240Bytes

CARATTERISTICHE SOFTWARE

Quality of Service: Support Port Based/802.1p Based priority – Support 4 priority queues – Rate Limit – Storm Control

Caratteristiche L2: IGMP Snooping – Link Aggregation – Port Mirroring – Cable Diagnostics – Loop Prevention

VLAN: Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) – MTU/Port/Tag VLAN

Metodo di trasmissione: Store-And-Forward

ALTRO

Certificazioni: FCC, CE, RoHS

Contenuto della confezione: TL-SG1016DE – Power Cord – Installation Guide – Resource CD – Rackmount Kit – Rubber Feet

Requisiti di sistema: Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ Windows 7 or Windows 8, MAC® OS, NetWare®, UNIX® or Linux.

Ambiente: Operating Temperature: 0,~40, (32,~104,)

Storage Temperature: -40,~70, (-40,~158,)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Meta Fields

SKU : 43.6681

REGULAR PRICE : 93.2