



SWITCH 24P LAN GIGABIT TP-LINK TL-SG1024DE EASY SMART SWITCH

Description

CARATTERISTICHE HARDWARE

Standards e protocolli: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p

Interfaccia: 24 10/100/1000Mbps RJ45 Ports

AUTO Negotiation/AUTO MDI/MDIX

Cablaggio: 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

100BASE-TX: UTP category 5, 5e cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

Ventilazione: Fanless

Dimensioni (LxPxA): 11.6*7.1*1.7 in. (294*180*44 mm)

Alimentatore: 100-240VAC, 50/60Hz

PRESTAZIONI

Switching Capacity: 48Gbps

Tavola indirizzi MAC: 8K

Packet Buffer Memory: 512KB

Packet Forwarding Rate: 35.7Mpps

Jumbo Frame: 10240Bytes

CARATTERISTICHE SOFTWARE

Quality of Service: Support Port Based/802.1p Based priority

Support 4 priority queues

Rate Limit

Storm Control

Caratteristiche L2: IGMP Snooping

Link Aggregation

Port Mirroring

Cable Diagnostics

Loop Prevention

VLAN: Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs)

MTU/Port/Tag VLAN

Metodo di trasmissione: Store-And-Forward

ALTRO

Certificazioni: FCC, CE, RoHS

Contenuto della confezione: TL-SG1024DE, Power Cord, Installation Guide, Resource CD, Rackmount Kit, Rubber Feet

Requisiti di sistema: Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ Windows 7 or Windows 8, MAC® OS, NetWare®,

UNIX® or Linux.

Ambiente: Operating Temperature: 0°~40° (32°~104°)

Storage Temperature: -40°~70° (-40°~158°)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Meta Fields

SKU : 43.7501

REGULAR PRICE : 118.61