



SWITCH 5P LAN 10/100M (4P POE FINO 64W) ATLANTIS A02-F5POE4-

Description

Product Name

NetPower F5PoE 4-A

Code

A02-F5PoE4-A

Standard

IEEE 802.3 10BASE-T Ethernet

IEEE 802.3u 100BASE-TX Fast Ethernet

IEEE 802.3af (Mode A) [PoE: pin 3,6 for power- and pin 1,2 for power+]

IEEE 802.3x Flow Control

Network Media

- 10Base-T: UTP category 3, 4, 5 cable Unshielded Twisted Pair (UTP) Cable
- 100Base-TX: UTP category 5, 5e cable Unshielded Twisted Pair (UTP) Cable
- PoE port: UTP category 5 Unshielded Twisted Pair (UTP) Cable

Protocol

CSMA/CD

Topology

Star

Ports

- 5 x 10/100 Mbps Auto-Negotiation, Auto-MDIX Ports (port 1-9)
- 4 x 10/100 Mbps Auto-Negotiation, Auto-MDIX PoE Ports (port 1-8)

Network Data Transfer Rate

Ethernet: 10Mbps (half duplex), 20Mbps (full duplex)

Fast Ethernet: 100Mbps (half duplex), 200Mbps (full- duplex)

Diagnostic LEDs

Power, Link/ACT, PoE

PoE (Power over Ethernet)

- Up to 15.4W per port
- PoE power up to 48W for all 4 PoE ports
- PD classification identify
- PoE Over Current Protection

- PoE Circuit Sorting Protection

Filtering Address Table

2K entries per device

RAM Buffer Size

96KBytes (768Kbit) per device

Internal Power Adapter

- 100-240 V AC/50-60Hz

Power Consumption

- 8.0 Watt (Maximum without PD device connected)
- 54 Watt (Maximum with 48W PoE device connected)

Dimensions (WxHxD)

180mm × 114mm × 35mm

Weight

572 g

Temperature Range

- Operation: 0°C ~ 32°C
- Storage: -10°C ~ 60°C

Humidity

- Operation: 10% ~ 90% non-condensing
- Storage: 5% ~ 95% non-condensing

Meta Fields

SKU : 43.1171

REGULAR PRICE : 25.23

SALE PRICE : 22.71