



SWITCH 8P LAN GIGABIT TP-LINK TL-SG108PE EASY SMART 4P POE I

Description

Standards and Protocols IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p

Interface 8 10/100/1000Mbps RJ45 Ports

AUTO Negotiation/AUTO MDI/MDIX

Network Media 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

100BASE-TX: UTP category 5, 5e cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)

EIA/TIA-568 100? STP (maximum 100m)

Fan Quantity Fanless

Power Supply External Power Adapter(Output: 48VDC / 1.25A)

Power Consumption Maximum (PoE on): 65.2W (220V/50Hz)

Maximum (PoE off): 5.2W (220V/50Hz)

PoE Ports (RJ45) Standard: 802.3 af compliant

PoE Ports: Port 1- Port 4

PoE Power Budget: 55W

PERFORMANCE

Switching Capacity 16Gbps

Packet Forwarding Rate 11.9Mpps

MAC Address Table 4K

Packet Buffer Memory 1.5Mb

Jumbo Frame 15KB

SOFTWARE FEATURES

Quality of Service Support Port-Based/802.1p/DSCP priority

Support 4 priority queues

Rate Limit

Storm Control

L2 Features IGMP Snooping V1/V2/V3

Link Aggregation

Port Mirroring

Cable Diagnostics

Loop Prevention

VLAN Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs)

MTU/Port/Tag VLAN

Management Web-based GUI

Easy Smart Configuration Utility

Transmission Method Store-And-Forward

OTHERS

Certification FCC, CE, RoHS

Package Contents TL-SG108PE

Power Adapter

Installation Guide

Resource CD

Rubber Feet

System Requirements Microsoft® Windows® for running Utility

Environment Operating Temperature: 0?~40? (32?~104?)

Storage Temperature: -40?~70? (-40?~158?)

Operating Humidity: 10%~90%RH non-condensing

Storage Humidity: 5%~95%RH non-condensing

Meta Fields

SKU : 43.5825

REGULAR PRICE : 81.33