



UPS ATLANTIS A03-HP1502 1500VA/750W SINEWAVE UPS+STABILIZ+FI

Description

1500

750

- Voltage: 162-290V
- Frequency: 50Hz±5%
- Voltage: 220V(±10%) [AC] / 220V(±7%) [INV]
- Frequency: 50Hz (±1%)
- AVR: Built-in
- Waveform: Pure SineWave
- Less than 2-6 ms (typical), 10 Max
- Total Efficiency Over 80%
- Voltage 24VDC
- Capacity 12V/7.2Ah
- Quantity 2
- Recharge Time 6 hours to (90%)
- Type Sealed Maintenance Free
- Lead Acid VRLA Type

Input Voltage, Output Voltage, Load Level Indicator, Overload, Utility Normal, Backup, Battery Low and Battery Fault conditions

- Overload AC Buzzer continuously alarms then UPS shuts down after 10 seconds (>110%)
- Overload Inverter UPS shuts down after 10 seconds (>110%)
- Short Circuit INV Input Fuse & Electric Circuit
- Short Circuit AC Electric Circuit
- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off
- Modem (RJ11) & LAN (RJ45)
- Spike Suppression Meets EN61000-4-5
- Noise Suppression Meets EN50991-1
- Battery Mode (sound every 10 seconds)
- Low Battery (sound every seconds)
- OverLoad (sound every 0.5 seconds)
- Battery Replacement Alarm (sound every 2 seconds)
- Fault (continuously sounding)

- Output 2xIEC (Battery Power Supplied)
- Output 2xSchuko (Battery Power Supplied)
- Computer USB

Less than 45dB

10 to 30 mins for typical PC Load

146 x 160 x 350 mm

9.0 Kg (with Battery)

- Temperature 0°-40° C

- Humidity 0-95% (non-condensing)

Meta Fields

SKU : 42.9150

REGULAR PRICE : 279.2