



UPS ATLANTIS A03-HP3002 3000VA/1500W SINEWAVE UPS+STABILIZ+F

Description

3000

1500

- Voltage: 162-290V
- Frequency: 50Hz $\pm$ 5%
- Voltage: 220V($\pm$ 10%) [AC] / 220V($\pm$ 7%) [INV]
- Frequency: 50Hz ($\pm$ 1%)
- AVR: Built-in
- Waveform: Pure SineWave
- Less than 2-6 ms (typical), 10 Max
- Total Efficiency Over 80%
- Voltage 24VDC
- Capacity 12V/10.0Ah
- Quantity 2
- Recharge Time 6 hours to (90%)
- Type Sealed Maintenance Free
- Lead Acid VRLA Type

Input Voltage, Output Voltage, Load Level Indicator, Overload, Utility Normal, Backup, Battery Low and Battery Fault conditions

- Overload AC Buzzer continuously alarms then UPS shuts down after 10 seconds ($>$ 110%)
- Overload Inverter UPS shuts down after 10 seconds ($>$ 110%)
- Short Circuit INV Input Fuse & Electric Circuit
- Short Circuit AC Electric Circuit
- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off
- Modem (RJ11) & LAN (RJ45)
- Spike Suppression Meets EN61000-4-5
- Noise Suppression Meets EN50991-1
- Battery Mode (sound every 10 seconds)
- Low Battery (sound every seconds)
- OverLoad (sound every 0.5 seconds)
- Battery Replacement Alarm (sound every 2 seconds)
- Fault (continuously sounding)

- Output 6xIEC (Battery Power Supplied)
- Computer USB/RS232
- Less than 55dB (Active FAN)

10 to 30 mins for typical PC Load
205 x 160 x 400 mm
13.7 Kg (with Battery)
• Temperature 0°-40° C
• Humidity 0-95% (non-condensing)

Meta Fields

SKU : 42.9180

REGULAR PRICE : 377.41