



UPS ATLANTIS A03-PS700 700VA/300W SERVER LINE INTERACTIVE –

Description

Model: A03-PS700
Power Rating (VA): 700
Power Rating (W): 300

INPUT

Voltage: 180-270V
Frequency: 50Hz $\pm$ 5%

OUTPUT

Voltage: 220V($\pm$ 20%) [AC] / 220V($\pm$ 10%) [INV]
Frequency: 50Hz ($\pm$ 1%)
Waveform Simulated SineWave

TRANSFER Line/Battery
Less than 2-6 ms (typical)

EFFICIENCY

Total Efficiency Over 80%

BATTERY

Voltage 12VDC
Capacity 12V/5.0Ah
Quantity 1
Recharge Time 8 hours to (90%)
Type Sealed Maintenance Free Lead Acid VRLA Type

INDICATORS(LED Display)

AC Mode (Green lighting)
Battery mode (Green flashing every 10 seconds)
Low Battery (Green flashing every seconds and RED lighting)
Fault (Red lighting)

PROTECTION

Overload AC Buzzer continuously alarms then UPS shuts down after 10 seconds ($>$ 110%)
Overload Inverter UPS shuts down after 10 seconds ($>$ 110%)
Short Circuit INV Input Fuse & Electric Circuit
Short Circuit AC Electric Circuit

Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off

Modem RJ11

Spike Suppression Meets EN61000-4-5

Noise Suppression Meets EN50991-1

ALARM

Battery Mode (sound every 10 seconds)

Low Battery (sound every seconds)

OverLoad (continuously sounding)

Fault (continuously sounding)

CONNECTIONS

Output 2xIEC (Battery Power Supplied)

Backup Time

10 to 30 mins for typical PC Load

MECHANICAL

Dimensions (WxHxD): 166 x 87 x 161 mm

Net Weight(with Battery): 3 Kg

ENVIRONMENTS

Temperature 0°-40° C

Humidity 0-95% (non-condensing)

Package Contents

- OnePower Smart UPS
- Manual (Italian, English and French)
- Warranty and WEEE Instructions

CERTIFICATION

CE

Meta Fields

SKU : 42.931

REGULAR PRICE : 71.58