



UPS ATLANTIS A03-S2001 2000VA/1200W LINEINTERACTIVE UPS STAB

Description

Power Rating (VA)
2000

Power Rating (W)
1200

Input
Voltage: 160-290V
Frequency: 50Hz $\pm$ 5%

Output
Voltage: 190-245 [AC/AVR] / 220V($\pm$ 7%) [Battery]
Frequency: 50Hz ($\pm$ 1%)
AVR: Built-in
Waveform: Simulated SineWave

Transfer Line/Battery
Less than 4ms (typical)

Efficiency Battery
Total Efficiency Over 80%
Voltage: 24VDC
Capacity: 12V/9.0A
Quantity: 2
Recharge Time: 6-8 hours to (90%)
Type: Sealed Maintenance Free Lead Acid VRLA Type

Indicators
LCD: Utility Normal, Backup, Battery Load, Battery Voltage, Input Voltage, Output Voltage, Load, AVR and Battery/Fault conditions

Protection

- Overload AC Buzzer continuously alarms
- Overload Inverter Buzzer continuously alarms
- Short Circuit INV Input Fuse & Electric Circuit
- Short Circuit AC Electric Circuit
- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off
- Spike Suppression: Meets EN61000-4-5

– Noise Suppression: Meets EN50991-1

Connections

Output: 4 x IEC + 1 Schuko (Battery Power Supplied)

Computer: USB (USB Cable isn't included)

Backup Time

10 to 30 mins for typical PC Load

Mechanical

Dimensions (WxHxD): 148 x 198 x 315 mm

Net Weight (with Battery): 12 Kg

Environments

Temperature: 0-40° C

Humidity: 0-95% (non-condensing)

Certification

CE

Meta Fields

SKU : 42.943

REGULAR PRICE : 209.05