

## VENTOLA X CPU COOLER MASTER RR-TX3E-22PK-R1 HYPERTX3EVO INT

### Description

- 3 direct contact heat pipes with a base that is engineered to minimize CPU contact gaps – providing excellent heat conduction.
- Option for adding 2nd fan with quick-snap fan brackets to increase cooling performance.
- A mere 17 dBA (minimum speed) is accomplished by utilizing a silent 92mm PWM fan with a wide RPM range.
- Versatile all-in-one mounting solution supporting the latest Intel® LGA 1366 / 1155 / 1151 / 1150 and AMD FM2 / FM1 / AM3+.
- Excellent airflow design with compact heat sink dimension

### Model

RR-TX3E-28PK-R1 / RR-TX3E-22PK-R1

### CPU Socket

#### Intel Socket:

LGA 1366 / 1156 / 1155 / 1151 / 1150 / 775 \*

#### AMD Socket:

FM2+ / FM2 / FM1 / AM3+ / AM3 / AM2+ / AM2

### CPU Support

#### Intel:

Core™ i7 Extreme / Core™ i7 / Core™ i5 / Core™ i3 / Core™2 Extreme / Core™2 Quad / Core™2 Duo / Pentium / Celeron

#### AMD:

FX-Series / A-Series / Phenom™ II X4 / Phenom™ II X3 / Phenom™ II X2 / Phenom™ X4 / Phenom™ X3 / Athlon™ II X4 / Athlon™ II X3 / Athlon™ II X2 / Athlon™ X2 / Athlon™ / Sempron™ / AM4

### Dimension

90 x 79 x 136 mm

### Heat Sink Dimensions

90 x 51 x 136 mm

### Heat Sink Material

3 Direct Contact Heat Pipes / Aluminum Fins

### Heat Sink Weight

306g

### Heat Pipes Dimensions

ø6mm

Fan Dimension

92 x 92 x 25 mm

Fan Speed

800 – 2,200 RPM (PWM) ± 10% (EU Version)

Fan Airflow

15.7 – 43.1 CFM ± 10% (EU Version)

Fan Air Pressure

0.35 – 2.63mm H<sub>2</sub>O ± 10% (EU Version)

Fan Life Expectancy

40,000 hours

Fan Noise Level (dB-A)

17 – 30 dBA (EU Version)

Bearing Type

Long Life Sleeve Bearing

Connector

4-Pin

Fan Rated Voltage

12 VDC

Fan Rated Current

0.15A (EU Version)

Power Consumption

1.8W (EU Version)

Fan Weight

73g

Note \* Supplied accessories may differ by country or area. Please check with your local distributor for further details.

**Meta Fields**

**SKU :** 89.1165

**REGULAR PRICE :** 32.93