



VIDEOCAMERA HIKVISION DS-2CE19D3T-IT3ZF(2.7-13MM) TURBO HD 4

Description

Camera

WDR (Wide Dynamic Range): > 120 dB

Image Sensor: 2.0 megapixel progressive scan CMOS

Signal System: PAL/NTSC

Effective Pixels: 1920(H)*1080(V)

Min. Illumination: Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR

Shutter Time: PAL: 1/25 s to 1/50, 000 s

NTSC: 1/30 s to 1/50, 000 s

Slow Shutter: Max. 16 times

Lens: 2.7 mm to 13.5 mm motorized varifocal lens

Lens Mount: ?14

Adjustment Range: Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°

Day& Night: IR cut filter

Video Frame Rate: PAL: [1080p@25fps](#)

NTSC: [1080p@30fps](#)

Synchronization: Internal Synchronization

Lens

Horizontal Field of View: 102° to 31°

Menu

Image Mode: STD/HIGH-SAT

3D DNR (Digital Noise Reduction): Level 1 to 9

D/N Mode: Auto/Color/BW (Black and White)

BLC: Yes

AGC: High/Medium/Low/Off

HLC: Yes

WDR: Yes

Language: English

Function: Brightness, Sharpness, 3D DNR, Mirror, Smart IR

Interface

Switch Button: TVI/AHD/CVI/CVBS

Video Out: 1 HD analog output

General

Material: Front cover: Metal

Main body: Plastic

Bracket: Metal

Operation Condition: -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)

Power Supply: 12 VDC±25%

Power Consumption: Max. 7.7 W

Weather Proof: IP67

IR Range: Up to 70 m

Dimension: 84.5 mm × 92 mm × 255.1 mm (3.33" × 3.62" × 10")

Meta Fields

SKU : 47.2131

REGULAR PRICE : 87.75