



VIDEOCAMERA IP ATLANTIS A11-905A-DP BIANCA-4MPIXEL SUPP.POE-

Description

Product Name
NetCamera 905A-DP

Code
A11-905A-DP

Resolution
4 MegaPixel

Type
Dome

Protocol
Onvif, I8S, RTSP

Lan Interface
RJ-45 Ethernet 10/100 Base-T

PoE
YES Mode A

Chipset
Omnivision Hi3516D+OV4689

Sensor
1/3" CMOS

Min Illumination
0 LUX with IR ON

IR Distance
1 LED Array (IR 850nm) Up to 12mt

IR Filter
Mechanical IR Cut Filter (light Sensor)

LENS
4.0 mm fixed lens (55° Horizontal)

Streaming

2 (codec=H.264 or H.265) [FrameRate / Bandwith / Unicast / Multicast]

Resolution

Main Stream: • 4MP (2592×1520)@20fps • 3MP (2048×1520)@25fps • HD1080P(1920×1080)@25fps

Sub Stream: • D1-P(720×576)@25fps • VGA(640×480)@25fps • Q720P(640×352)@25fps • QVGA(320×240)@25fps

Video Parameters

Horizontal/Vertical Mirror, 90°/180°/270° Rotation, Color Mode (Normal/Bright/Nature), WDR SW (3 level), Defogging (3 Level), Sharpness, Slow Shutter, Exposure Control (automatic/manual), Gamma, Anti-Flicker (50Hz, 60Hz, Close)

Access

Multiple user access levels with password protection

Max Users

- 5 simultaneous users
- Unlimited number of users using multicast
- 2 differnt users (Admin, Guest)

Network

NTP, DynDNS, PPPoE, SMTP, UPnP

Management

WEB, I8S (NVR), ONVIF (CMS, NVR)

Remote View

WEB (ActiveX), Onvif CMS, i8(CMS), RTSP

Alarm

Mail(SMTP), CMS

Advanced

- Scheduled AutoReboot
- Motion Detection (5 Level)
- Tampering Detection (3 level)

CMS (x Windows)

CMS (up to 16 cameras)

Waterproof Rating

IP66

Dimensions (DxH)

90 × 100 mm

Weight

380 g

Temperature Range

-10°C ~ 40°C RH 85% Max

Housing

Metal

Power Supply

DC12V, 1000mA max or Using PoE Mode A

Meta Fields

SKU : 47.9645

REGULAR PRICE : 164.15

SALE PRICE : 89.55