



VIDEOCAMERA IP HIKVISION DS-2CD1043G0-I(4MM)EASY IP1.0+ BULL

Description

Camera

Image Sensor: 1/3" Progressive Scan CMOS

Min. Illumination: Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)

Shutter time: 1/3 s to 1/100,000 s

Slow shutter: Yes

Lens: 2.8 mm, 4 mm, 6 mm

2.8 mm, horizontal FOV 100°, vertical FOV 55°, diagonal FOV 117°

4 mm, horizontal FOV 77°, vertical FOV 42°, diagonal FOV 88°

6 mm, horizontal FOV 51°, vertical FOV 28°, diagonal FOV 58°

Lens Mount: M12

Adjustment Range: Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°

Day& Night: IR Cut Filter

Wide Dynamic Range: 120 dB

Digital noise reduction: 3D DNR

Compression Standard

H.265 Type: Main Profile

Video Compression: H.265/H.264/MJPEG

H.264 code profile: Baseline Profile/Main Profile/High Profile

Video bit rate: 32Kbps~8Mbps

Image

Max. Image Resolution: 2560 × 1440

Frame Rate: 50Hz: 20fps (2560 × 1440), 25fps (2304 × 1296, 1920 × 1080, 1280 × 720)

60Hz: 20fps (2560 × 1440), 30fps (2304 × 1296, 1920 × 1080, 1280 × 720)

Sub Stream: 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Image Enhancement: BLC, 3D DNR

Image Settings: Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser

ROI: 1 fixed region for main stream and sub-stream

Day/Night Switch: Auto, scheduled

Network

General Function: Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter

Network Storage: NAS (Support NFS,SMB/CIFS)

Alarm Trigger: Motion detection, video tampering alarm, illegal login

Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour

System Compatibility: ONVIF (Profile S, Profile G), ISAPI

Interface

Communication Interface: 1 RJ45 10M/100M self-adaptive Ethernet port

General

Operation Condition: -30 °C to 50 °C (-22 °F to 122 °F), humidity: 95% or less (non-condensing)

Power Supply: 12 VDC $\pm$ 25%, PoE (802.3af Class3)

Power Consumption: 12 VDC, 0.4 A, Max: 5 W

PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.13 A, Max: 7 W

Weather Proof: IP67

IR Range: Up to 30m

Dimensions: Camera: Ø 70 mm × 172.7mm (2.7? × 6.8?)

With package: 216 mm × 121 mm × 118 mm (8.5? × 4.8? × 4.6?)

Weight: Camera: approx. 280 g (0.62 lb.)

With package: approx. 530 g (1.17 lb.)

Meta Fields

SKU : 47.2102

REGULAR PRICE : 120.79

SALE PRICE : 120.78