



VIDEOCAMERA IP HIKVISION DS-2CD1643G0-IZ(2.8-12MM)EASY IP1.0

Description

Camera

Image Sensor: 1/2.8" Progressive Scan CMOS

Min. Illumination: Color: 0.01 Lux @(F1.2, AGC ON), 0.017 Lux @(F1.6, AGC ON), 0 Lux with IR

Shutter time: 1/3 s to 1/100,000 s

Slow shutter: Support

Lens: 2.8 mm to 12 mm @F1.6 ,

horizontal field of view: 111.5° to 33°

vertical field of view: 58° to 18.5°

diagonal field of view: 134° to 38°

Lens Mount: ?14

Adjustment Range: Pan: 0° to 360°, tilt: 0° to 90°, rotation: 0° to 360°

Day& Night: IR cut filter with auto switch

Wide Dynamic Range: Digital WDR

Digital noise reduction: 3D DNR

Compression Standard

Video Compression: H.264/MJPEG

H.264 code profile: Baseline Profile/Main Profile

Video bit rate: 32Kbps~8Mbps

Image

Max. Image Resolution: 1920 x 1080

Frame Rate: 50Hz: 25fps (1920 x 1080, 1280 x 960, 1280 x 720)

60Hz: 30fps (1920 x 1080, 1280 x 960, 1280 x 720)

Sub Stream: 50Hz: 25fps (640 x 480, 640 x 360, 320 x 240)

60Hz: 30fps (640 x 480, 640 x 360, 320 x 240)

Image Enhancement: BLC, 3D DNR

Image Settings: Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

Day/Night Switch: Day, Night, Auto, Scheduled

Network

General Function: Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark

Alarm Trigger: Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error

Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour

System Compatibility: ONVIF (Profile S, Profile G), ISAPI

Interface

Communication Interface: 1 RJ45 10M/100M self-adaptive Ethernet port

Video Output: 1Vp-p Composite Output (75 Ω, BNC)

On-board storage: Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

Reset Button: Yes

General

Operating Conditions: -30 °C ~ 60 °C (-22 °F ~ 140 °F)

Humidity 95% or less (non-condensing)

Power Supply: 12 VDC $\pm$ 25%, PoE (802.3af Class3)

Power Consumption: 12 VDC, 0.9 A, max: 11W

PoE: (802.3af, 36V-57V), 0.4 A to 0.2 A, Max: 12.9W

Weather Proof: IP67

IR Range: Up to 30m

Dimensions: 105 mm $\times$ 244.4 mm (4.1" $\times$ 9.6")

Weight: 705 g (1.6 lb.)

Meta Fields

SKU : 47.2103

REGULAR PRICE : 248.12