



WIRELESS ACCESS POINT UBIQUITI UNIFI UAP-AC-LITE-5 DUALBAND

Description

UNIFI

Dimensions 160 x 160 x 31.45 mm (6.30 x 6.30 x 1.24?)

Weight 170 g (6.0 oz), 185 g (6.5 oz) with Mounting Kits

Networking Interface (1) 10/100/1000 Ethernet Port

Ports No

Buttons Reset

Antennas (2) Dual-Band Antennas, 3 dBi Each

Wi-Fi Standards 802.11 a/b/g/n/ac

Power Method Passive Power over Ethernet (24V), (Pairs 4, 5+; 7, 8 Return)

Power Supply 24V, 0.5A Gigabit PoE Adapter

Maximum Power Consumption 6.5W

Max TX Power 20 dBm

BSSID Up to Four per Radio

Power Save Supported

Wireless Security WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)

Certifications CE, FCC, IC

Mounting Wall/Ceiling (Kits Included)

Operating Temperature -10 to 70° C (14 to 158° F)

Operating Humidity 5 to 95% Noncondensing

ADVANCED TRAFFIC MANAGEMENT

VLAN 802.1Q

Advanced QoS Per-User Rate Limiting

Guest Traffic Isolation Supported

WMM Voice, Video, Best Effort, and Background

Concurrent Clients 200+

SUPPORTED DATA RATES (MBPS)

802.11a 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n 6.5 Mbps to 300 Mbps (MCS0 – MCS15, HT 20/40)

802.11ac 6.5 Mbps to 867 Mbps (MCS0 – MCS9 NSS1/2, VHT 20/40/80)

802.11b 1, 2, 5.5, 11 Mbps

802.11g 6, 9, 12, 18, 24, 36, 48, 54 Mbps

Meta Fields

SKU : 52.5230

REGULAR PRICE : 438.54