



WIRELESS N WALL-PLATE ACCESS POINT 300M TP-LINK EAP115-WALL

Description

CARATTERISTICHE HARDWARE

Interfaccia: 10/100Mbps Ethernet (RJ-45) Port *2
Tasto: LED/Wi-Fi Button?RESET
Alimentazione: PoE(IEEE 802.3af)
Consumo energetico: 2.8 W
Dimensioni (L x P x A): 3.4×3.4×1.2 in. (86.8*86.8*30.2 mm)
Tipo di antenna: Internal 2*1.8dBi Omni
Tipo di montaggio: Wall Plate Mounting
Physical security lock: –
Watch dog: Yes
Hardware Watch Dog: Yes

CARATTERISTICHE WIRELESS

Standard wireless: IEEE 802.11n/g/b/a
Frequenza: 2.4GHz
Signal rate:
11n: Up to 300Mbps(dynamic)
11g: Up to 54Mbps(dynamic)
11b: Up to 11Mbps(dynamic)
Potenza di trasmissione: CE??20dBm(2.4GHz)
Funzionalità wireless:
Multiple SSIDs?Up to 8 SSIDs?
Enable/Disable Wireless Radio
Automatic Channel Assignment
Transmit Power Control (Adjust Transmit Power on dBm)
QoS(WMM)
Load Balance
Rate Limit
Reboot Schedule
Wireless Schedule
Wireless Statistics based on SSID/AP/Client
Sicurezza wireless:
Captive Portal Authentication
Access Control
Wireless Mac Address Filtering
Wireless Isolation Between Clients
SSID to VLAN Mapping

Rogue AP Detection
802.1X Support
64/128/152-bit WEP / WPA / WPA2-Enterprise,
WPA-PSK / WPA2-PSK

GESTIONE

Controller EAP: Yes
Avvisi e-mail: Yes
LED ON/OFF: Yes
Management MAC Access Control: Yes
SNMP: v1,v2c
Log di sistema locale e remoto: Local/Remote Syslog
Telnet: Yes
Gestione web-based: HTTP/HTTPS
L3 Management: Yes
Multi-site Management: Yes
Management VLAN: Yes

ALTRO

Certificazione: CE, RoHS
Contenuto della confezione:
300Mbps Wireless N Wall-Plate Access Point EAP115-Wall
Installation Guide
Mounting Screw
Requisiti di sistema: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Ambiente:
Operating Temperature: 0?~40? (32?~104?)
Storage Temperature: -40?~70? (-40?~158?)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing

Meta Fields

SKU : 43.6719
REGULAR PRICE : 37.33
SALE PRICE : 36.59