



WIRELESS ROUTER "N"ADSL2+ TP-LINK TD-W8961N (ANNEX A) 300M 8

Description

CARATTERISTICHE HARDWARE

Interfaccia: 4 10/100Mbps RJ45 Ports

1 RJ11 Port

Tasto: 1 Power On/Off Switch

1 WPS Button

1 Wi-Fi On/Off Button

Alimentatore esterno: 9VDC/0.85A

Standard IEEE: IEEE 802.3, 802.3u

Standard ADSL: Full-rate ANSI T1.413 Issue 2,

ITU-T G.992.1(G.DMT),

ITU-T G.992.2(G.Lite)

ITU-T G.994.1 (G.hs),

ITU-T G.995.1

Standard ADSL2: ITU-T G.992.3 (G.dmt.bis),

ITU-T G.992.4 (G.lite.bis)

Standard ADSL2+: ITU-T G.992.5

Dimensioni (L x P x A): 7.7 * 5.1 * 1.4 in. (195 * 130 * 35 mm)

Tipo di antenna: Omni directional, Fixed

Guadagno antenna: 2x5dBi

CARATTERISTICHE WIRELESS

Standard wireless: IEEE 802.11n, 802.11g, 802.11b

Frequenza: 2.400-2.4835GHz

Potenza di trasmissione: Sicurezza wireless: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK,

Wireless MAC Filtering

CARATTERISTICHE SOFTWARE

QoS (Quality of Service): QoS Remarking based on IPP/ToS, DSCP and 802.1p

Sicurezza: NAT Firewall,

SPI Firewall,

MAC / IP / Packet / Application / URL Filtering,

Denial of Service(DoS),

SYN Flooding,

Ping of Death

Gestione: Web Based Configuration(HTTP),

Remote management,

Telnet management,

Command Line Interface,

SSL for TR-069,

SNMP v1/2c,

SNMP over EOC,
Web Based Firmware Upgrade,
CWMP(TR-069),
Diagnostic Tools
Port forwarding: Virtual Server, DMZ, ACL(Access Control List)
VPN pass-through: PPTP, L2TP, IPSec Pass-through
Protocolli ATM/PPP: ATM Forum UNI3.1/4.0,
PPP over ATM (RFC 2364),
PPP over Ethernet (RFC2516),
IPoA (RFC1577/2225),
PVC – Up to 8 PVCs
Caratteristiche avanzate: Traffic Shaping(ATM QoS) UBR, CBR, VBR-rt, VBR-nrt;
Dynamic Host Configuration Protocol (DHCP), DHCP relay;
Network Address Translation (NAT);
PVC/Ethernet Port Mapping
VLAN, 802.1P,
Static Routing, RIP v1/v2 (optional);
DNS Relay, DDNS,
IGMP snooping V1/2
IGMP Multicast,
UPnP
ALTRO
Certificazione: CE, FCC, RoHS
Contenuto della confezione: TD-W8961N
External Splitter
RJ-11 Telephone Cable
RJ-45 Ethernet Cable
Quick Installation Guide
Resource CD
Power Adapter
Requisiti di sistema: Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ ?Windows 7 or Windows 8, MAC® OS,
NetWare®, UNIX® or Linux.
Ambiente: Operating Temperature: 0?~40? (32?~104?)
Storage Temperature: -40?~70? (-40?~158?)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing

Meta Fields

SKU : 43.6698

REGULAR PRICE : 19.53